

Oplight

■ F4681009 - Textured White

Designed by Jasper Morrison

Indirect light wall lamp. Body in die-cast aluminium with powder coating. Diffusor made of injection-moulded polycarbonate semi-transparent. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Oplight is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.



Main specifications

| | | | |
|---------------------------------|------------------------------|---------------------------|------|
| Mounting | Wall | Dimmable | Yes |
| Environment | Indoor dry location | Autoprotected Lamp | No |
| Light source type | LED | Number of heads | 1 |
| Light source replaceable | Non-replaceable light source | Source Power (W) | 16 |
| | LED Module | System Flux (lm) | 1325 |

Optical

| | |
|------------------------------|-----------|
| Lighting Type | Indirect |
| Lighting distribution | Symmetric |
| CCT (K) | 2700K |
| CRI> | 90 |
| Cold Beam Lighting | No |
| Extreme Cut off | No |

Electrical

| | |
|---------------------------|---------------------------------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main Voltage (Vac) | 220-240 |
| Dimmable | Yes |
| Dimming Interface | Remote Dimmable (Dimmer Not Included) |

Physical

| | | | |
|--------------------------|----------------|--------------------|----|
| Colour | Textured White | IP external | 20 |
| Length (mm) | 193 | | |
| Net weight (kg) | 0.9 | | |
| Gross weight (kg) | 1.98 | | |
| IP | 20 | | |